



Wall Mounted Hydronic 50Hz



Product

- Quiet operation
- Efficient cooling
- Air sweep
- Auto restart function
- Modern design compact size

Wireless Controller

- Elegant and slim design
- Vertical swing louver control
- LCD display
- Wireless 8m-11m transmission
- Operation modes (Auto/Cool/Dry/Fan)
- Timer ON/OFF
- Temperature control range 17C-30C
- Fan speeds selection
- Night light function



Wired Controller (Optional)

- Elegant design
- Large LCD display
- Operation modes (Auto/Cool/Dry/Fan)
- Timer ON/OFF
- Temperature control range 17C-30C
- Fan speeds selection
- Follow me feature
- 10m wire inclusive



Specifications

Wall Mounted Hydronic 50Hz

Model				HHH08P15-M	HHH10P15-M	HHH12P15-M	HHH15P15-M	HHH18P15-M
Air flow		H/M/L	CMH	425/360/320	510/430/380	680/580/510	850/720/640	1020/870/770
Cooling	Capacity	H/M/L	kW	2.2/1.84/1.65	2.64/2.24/2.05	3.08/2.62/2.27	4.07/3.73/3.24	4.45/4.18/3.74
	Water flow rate	H	l/h	378	454	530	700	765
	Water pressure drop	H	kPa	12	18	22	26	29
Power supply			V/ph/Hz	220-240/1/50				
Power input		H	W	28	40	44	50	60
Sound pressure level		H/M/L	dB(A)	30/24/20	35/29/24	37/31/26	39/33/28	40/34/29
Coil	Row			2				
	Max. Working pressure		Mpa	1.6				
	Diameter		mm	Φ7				
Body	Dimensions	W×H×D	mm	915×210×290			1070×210×316	
	Net weight		kg	12			15	
	Packing	W×H×D	mm	1020×300×385			1180×300×410	
	Gross weight		kg	16			19	
Pipe connection	Water inlet/outlet pipe		Inch	3/4"				
	Drain pipe		mm	ODΦ20				

Rating Conditions	Temperature
Indoor	80°F DB/ 67 °F WB
Chilled Water In/Out	45°F / 55 °F

Remark : the above design & specification may be subjected to changes without prior notification for product improvement
Note that chilled water control valve package is not inclusive
R12015